

2.4G WIFI

Color screen office Phone with wireless

FIP11W Datasheet



VoIP SoC	CPU Core: MIPS 580Mhz
Flash	16M Flash
RAM	64M SDRAM
Display	320x240 -TFT color screen Red color LEDs for call and message indication
Phone Keys	4 soft keys 13 function keys:MENU, MUTE ,SMS, HOLD,Volume+/-, Transfer, 3-way conferencing, Hands free Redial and so on. 5 navigate key 12 Dialing Buttons (0~9, *, #), 32 Multi-function keys



ULTRATIVE HK CO., LIMITED

E: sales@ultrative.com

T: +86-755-29630367

F: +86-755-29685231

http://www.ultrative.com

Power Supply	<p>AC/DC Adapter</p> <p>AC Input: 100~240V, 50~60Hz</p> <p>DC Output: 5V, 1A</p>
I/O Interfaces	<p>2 RJ-45 ports (Ethernet 10/100 Base-T)</p> <p>1 RJ9 earphone jack</p> <p>1 FXO port to connect PSTN line(only for L series)</p> <p>1 usb port</p> <p>802.11n 2T2R (Only for W series)</p> <p>Support PoE comply with IEEE802.3af(optional)</p>
Environmental	<p>Operation Temperature: 0~50 Degree C</p> <p>Storage Temperature: -25~ 85 Degree C</p> <p>Relative Humidity: 10%~90% No Condensing</p>
Audio Feature	<p>G.711 (A-Law, μ-Law)</p> <p>G.722(HD)</p> <p>G.723.1</p> <p>G.729AB</p> <p>G.726</p> <p>iLBC</p> <p>Adaptive Jitter Buffer Management</p> <p>Voice Activity Detection</p> <p>Comfort Noise Generation</p> <p>Echo Cancellation</p>
Protocols	<p>SIP V2 (RFC 3261,3262,3263,3264)</p> <p>SDP (RFC2327)</p> <p>RTP/RTCP (RFC1889 and RFC1890)</p> <p>NAPTR for SIP URI Lookup (RFC2915)</p> <p>STUN (RFC 3489)</p> <p>ARP/RARP (RFC 826/903)</p> <p>SNTP (RFC 2030)</p> <p>TFTP/HTTP/HTTPS for Auto Provisioning</p> <p>DNS/DNS SRV (RFC1706 and RFC 2782)</p> <p>IEEE802.1Q VLAN/802.1p and IP TOS</p> <p>SNMPV2</p> <p>TR069(TR104/TR098/TR111)</p>



ULTRATIVE HK CO., LIMITED

E: sales@ultrative.com

T: +86-755-29630367

F: +86-755-29685231

http://www.ultrative.com

<p>Applications</p>	<p>SMS Function MAC Address Cloning SIP proxy redundancy DNS SRV Direct IP to IP calling Traversal by STUN VPN: pptp,l2tp,OpenVPN QoS with Layer 2 and Layer 3 DHCP Server and Client IP conflict detection Support Mutil-Vlan</p>
<p>Management</p>	<p>Firmware Upgradeable Web Management Interface Password Management Local and Remote Syslog (RFC3164) Auto Provisioning: TFTP, HTTP and HTTPS SNTP Time Synchronization Multi User Level Auto Provision Support TR069 management mode</p>
<p>Call Features</p>	<p>8 lines Auto Answer 3-way Conference Music on hold Call Hold Call Forwarding Call Mute Call Transfer Call Waiting Call Pickup MWI CID and CWCID DTMF Relay: In-band, Out-band(RFC2833) and SIP Info Full-duplex Speakerphone Hotline Redial Dial Plan Volume adjustment- handset/hand free/speaker/ringing</p>



ULTRATIVE HK CO., LIMITED

E: sales@ultrative.com

T: +86-755-29630367

F: +86-755-29685231

<http://www.ultrative.com>

Phone feature	Customized Ring Tone SMS (100 records) Call History (100 records) <ul style="list-style-type: none">- Most Recently Missed Calls- Most Recently Received Calls- Most Recently Dialed Numbers Phone book (500 records)
SIZE	8.8cm(L)*8.5cm(W)*3.7cm(H)
Weight	625g (No packet) QTY/CTN: 10pcs N.W./CTN: 10.5kg G.W./CTN: 11.5kg Carton Size: 42*42*29 cm Item Size: 188*185*37mm N.W.: 0.63kg







ULTRATIVE HK CO., LIMITED

E: sales@ultrative.com

T: +86-755-29630367

F: +86-755-29685231

<http://www.ultrative.com>

