

2.4G WIFI

Standard Business IP Phone

IP622CW Datasheet



VoIP SoC	CPU Core: MIPS24KEc(360M)
Flash	16MBytes Flash
RAM	32MBytes SDRAM
Display	128×64 Graphic LCD with white back light
Phone Keys	2 Line keys and 4 Soft keys, MENU, UP,DOWN,MUTE/DEL, REDIAL HOLD, MSG, Headset, Hand free 12 Dialing Buttons (0~9, *, #) 10 Multi-functional key without BLF
LED	1 MSG LED 2 Line LED



ULTRATIVE HK CO., LIMITED

E: sales@ultrative.com
 T: +86-755-29630367
 F: +86-755-29685231
<http://www.ultrative.com>

Power Supply	AC/DC Adapter AC Input: 100~240V, 50~60Hz DC Output: 5V, 1A
I/O Interfaces	2 RJ-45 port (10/100 Ethernet Ports) 1 RJ9 for headset Support PoE comply with IEEE802.3af(optional) Headset jack and Wall-mount 802.11n 1T1R
Environmental	Operation Temperature: 0~50 Degree C Storage Temperature: -25~ 85 Degree C Relative Humidity:10%~90% No Condensing
Audio Codec	G.711 (A-Law, μ -Law) G.722 (HD) G.723.1 G.729AB G.726 iLBC Adaptive Jitter Buffer Management Voice Activity Detection Comfort Noise Generation Echo Cancellation
Protocols	SIP V2 (RFC 3261,3262,3263,3264) SDP (RFC2327) RTP/RTCP (RFC1889 and RFC1890) NAPTR for SIP URI Lookup (RFC2915) STUN (RFC 3489) ARP/RARP (RFC 826/903) SNTP (RFC 2030) TFTP/HTTP/HTTPS for Auto Provisioning DNS/DNS SRV (RFC1706 and RFC 2782) IEEE802.1Q VLAN/802.1p and IP TOS SNMPV2 TR069(TR104/TR098/TR111)
Management	Firmware Upgradeable Web Management Interface Password Management Local and Remote Syslog (RFC3164) Auto Provisioning: TFTP, HTTP and HTTPS SNTP Time Synchronization Multi User Level Auto Provision Support TR069 management mode
Applications	SMS Function MAC Address Cloning SIP proxy redundancy DNS SRV Direct IP to IP calling Traversal by STUN VPN: pptp,l2tp,OpenVPN QoS with Layer 2 and Layer 3 DHCP Server and Client IP conflict detection

**ULTRATIVE HK CO., LIMITED**

E: sales@ultrative.com

T: +86-755-29630367

F: +86-755-29685231

<http://www.ultrative.com>

Support Mutil-Vlan	
Call Features	2 lines Auto Answer 3-way Conference Music on hold Call Hold Call Forwarding Call Mute Call Transfer Call Waiting Call Pickup MWI CID and CWCID DTMF Relay: In-band, Out-band(RFC2833) and SIP Info Full-duplex Speakerphone Hotline Redial Dial Plan Volume adjustment- handset/handfree/speaker/ringing
Phone feature	Customized Ring Tone SMS (100 records) Call History (100 records) - Most Recently Missed Calls - Most Recently Received Calls - Most Recently Dialed Numbers Phone book (100 records) Speed Dial (10 records) (L) 191 x (W) 205 x (H) 75 mm 720g (without package)
Dimension	QTY/CTN: 10pcs N.W./CTN: 9.2kg G.W./CTN: 10kg Carton Size: 58*23*43 cm Item Size: 191*205*75 mm N.W.: 0.72kg



ULTRATIVE





ULTRATIVE HK CO., LIMITED

E: sales@ultrative.com

T: +86-755-29630367

F: +86-755-29685231

<http://www.ultrative.com>





ULTRATIVE HK CO., LIMITED

E: sales@ultrative.com

T: +86-755-29630367

F: +86-755-29685231

<http://www.ultrative.com>

