



Shenzhen Ultrative Technology Co., Ltd.

深圳顺驰通科技有限公司

T: +86-755-29685231

E: sales@ultrative.com

<http://www.ultrative.cn> | com

Add: 012#, 5/F, Block A, Hedong Bldg., Liutang Rd., Xixiang St., Bao An District, Shenzhen, China

## SIMBANK32 Datasheet



### SIM Bank

### Quick Details

- Place of Origin: Guangdong, China (Mainland)
- Brand Name: Ultrative or OEM
- Model Number: SIMBANK128
- Type: SIM BANK
- Voice Protocol: H.323 and SIP
- Frequency: GSM 850/900/1800/1900MHZ



- Slots SIM bank: 128
- Type: SIM BANK
- Codec: G.711 (A/u law), G.729A/B, G.723.1
- Color: Grey

## Specifications

- 128 Slots SIM bank/sim server / gateway / sms gateway / voip
- Remote and Centralized Management of SIM cards
- Hot swap


## Product Description

SIM Bank, a SIM Box for 32 SIM cards, communicates directly with GoIPs with no SIM cards installed onboard. It allows centralized management and safekeeping of SIM cards. Hot swapping of SIM cards are supported so that no service interruptions to other SIM cards are incurred. SIM cards can be assigned to GoIP channels manually or dynamically with scheduled re-allocation algorithms. Therefore, SIM cards can virtually be moved between GoIP channels that are installed in different locations. In addition, SIM cards can be disabled based on certain triggering conditions and spare SIM cards can then be assigned to those GoIP channels. This mechanism helps to protect SIM cards from blocking and maximize the GoIP channel utilization.

### Competitive Advantage

SIM Bank is highly scalable by using a SIM Server (a license-free utility software offered by Ultrative) to manage over 10,000 SIM cards. It offers many advanced features for SIM card management such as automatic status querying and recharging SIM cards. It is inevitable and valuable equipment for call termination service providers who require management of SIM cards intelligently and efficiently.

### Applications



### Basic Function

- Remote and centralized management of SIM cards
- No need to switch and recharge SIM cards on-site
- Hot swap of SIM cards without powering off the SIMBANK32
- Free DDNS service to support dynamic public IP
- Management of 32 SIM cards in standalone mode.
- Free SIM Server for management of over 10,000 SIM cards
- Counter measures for the techniques used for SIM card blocking
- Online firmware upgrade

### Key Features

- Open Standard VoIP Protocols (ITU H.323 V4 and IETF SIP V2)
- Single or Multiple Server Registrations
- Two 10/100 Ethernet for WAN / LAN connections
- GSM module for making GSM calls



Speech quality ensured by QoS at the Ethernet and IP layers and comprehensive jitter buffer

VLAN and QoS support

NAT Transversal and Router functions

Voice prompts, HTTP Web, Auto Provision support for configuration and updates

Highly stable embedded Linux operating system in high performance ARM 9 Processor

### Enhanced Features

Dynamic selection of codec

Advanced jitter buffer

Automatic traversal of NAT and firewall

VLAN / Qos

Router

Echo cancellation for Speakerphone

Comfort noise generation (CNG)

Voice activity detection (VAD)

Auto provisioning (requires auto provisioning server)

On line firmware upgrade

Multi-language support: English and Chinese

### Physical Features

Hardware	Parameters	Remark
Model	SIMBANK32	
Processor	ARM9 133MHZ	
DSP	VP-101-1 196MHz	
RAM	32M	
FLASH	4M	
Network Card	100/10BASE-T x2	
LED	operating and circuit light	
Power consumption	12V/DC	
Weight	0.75kg	
Size	28.5*14.5*5(cm)	
Operating Temperature	0—45℃	
Working Humidity	40%—90% non-condensation	
Color	grey	
SIM port	32	
RJ45 port	1	



<b>Speech Characteristics</b>	<b>Service Condition</b>	<b>Remark</b>
G.168 Echo cancellation	Support	16mS
g.723	Support	
g.711A/u	Support	
g.729A/B	Support	
GSM	Support	
PLC	Support	
CNG	Support	
VAD	Support	
Jitter Buffer	Support	
T.38	Support	
<b>Network Characteristic</b>	<b>Parameters</b>	<b>Remark</b>
<b>LAN Port</b>		
DHCP	Support	
PPPoE	Support	
Static IP	Support	
NAT Transversal	Relay or Port forwarding	Relay need coordinate with Ultrative Relay Server
Network time	NTP / SNTP	
10/100BASE-T	10/100 auto adaptation	
<b>PC Port</b>		
Static IP	Support	
DHCP	Max support 200 terminals	
10/100BASE-T	10/100 auto adaptation	
Switch mode	Support	
Protocols	ITU H.323 V4 and IETF SIP V2, SIP (RFC3261) TCP/UDP/IP, RTP/RTCP, HTTP, ARP/RARP, ICMP, DNS, DHCP, NTP, TFTP, TELNET, PPPoE	Support
<b>User Interface</b>	<b>Parameters</b>	<b>Remark</b>
Web page Configuration	HTTP	
Multiple password	3 password	Customized service



Shenzhen Ultrative Technology Co., Ltd.

深圳顺驰通科技有限公司

T: +86-755-29685231

E: sales@ultrative.com

<http://www.ultrative.cn> | com

Add: 012#, 5/F, Block A, Hedong Bldg., Liutang Rd., Xixiang St., Bao An District, Shenzhen, China

Keyboard setup	Support	
Online update	http	
Broadcast IP	Support	Chinese , English
Billing	Support	Coordinate with Ultrative Billing Software
Language	Chinese, English	
Multi-regional warning tone	China,HK,USA,UK,German etc.	
Warranty	One year	

Ultrative Communication