

# Two Lines Business IP Phone

## UTT-205 Datasheet



UTT-205 is a compact office IP phone with rich features. It has 128\*64 HD graphic LCD up to 4-line display; it also has HD Sound Quality, unique art design, demountable bracket to provide multi-angle, 9 programmable keys, and friendly user interface to satisfy users' communication needs.

### Login

Username: root  
Password: root

### Key Features

- Support 2 lines;
- Support demountable bracket to provide multi-angle;
- Support 9 programmable keys;
- Support Multi-language e.g. English, Chinese, Russian, Polish, Portuguesa, French, Brasil, Turkish.
- 2\*10/100M Ethernet ports, support POE;
- Auto-provision, HTTP/TFTP/FTP, TR069, PNP;

## Phone Features

- 2 SIP accounts, Hot line
- Call hold, Call waiting, Call forward, Call return; Call transfer (blind/busy/ask)
- Caller ID display, Redial, Mute, DND
- Auto-answer, 3-way conferencing
- Speed dial, SMS, Voicemail
- Tone scheme, Volume control
- Direct IP call without SIP proxy
- Ring tone selection/import/delete
- Black list, Hand-free indicator.
- Call history: dialed/received/missed (50 -entries);
- Soft keys programmable, Supports PC control
- Multi-Language: Chinese, English, French, Russian, Italian, Polish, Portuguesa, Portuguesa-Brasil, Spanish, Turkish

## Advanced Features

- 9 programmable keys (soft keys - 4, line key - 2, up / down / redial – 3)
- XML Phone Book search and input & output
- Enterprise phone book (800 entries)
- LDAP phone book

## IP PBX System Integration

- Busy lamp field (BLF), BLF list
- Bridged line appearance (BLA)
- DND & Forward synchronization
- Intercom, Paging, Music on hold
- Call pickup, Dial Plan, Call recording Anonymous call, Anonymous call rejection
- Network conference, Distinctive ring tone

## Codes and Voice Features

- Wideband Codec: G.722
- Narrowband codec: G.711 $\mu$ /A, G.723.1
- G.726, G.729AB, iLBC
- VAD, CNG, AEC, AGC
- Full-duplex

## Security

- LLDP, VPN(L2TP) ,802.1x
- Transport Layer Security (TLS)
- Digest authentication using MD5/MD5-sess
- Secure configuration file via AES encryption
- Phone lock for personal privacy protection
- Admin/User 2-level configuration mode

## Network Features

- SIP v1 (RFC2543), v2 (RFC3261)
- DNS SRV (RFC3263); IPv6
- NAT Traversal: STUN mode
- DTMF: In-Band, RFC2833, SIP Info, Auto
- HTTP/HTTPS Web Management
- IP Assignment: Static/DHCP/PPPoE
- Bridge/Router mode for PC port
- TFTP/DHCP/PPPoE client
- DNS client, NAT/DHCP server

## Management

- Auto-provision via FTP/TFTP/HTTP/HTTPS; PNP; SNMP V1/2 , TR069 optional
- Configuration: browser/phone/auto-provision
- Trace package and system log export

## Physical Features

- 128\*64 graphic LCD,
- 25 keys, including 9 programmable keys,
- 2 LEDs: 2\* account lights,
- 1\* RJ-9 handset port
- 1\*RJ-9 headset port(Optional)
- 2xRJ45 10/100M Ethernet ports
- Power adapter: AC 100~240V input and
- DC 5V/1A output
- Power over Ethernet ,IEEE 802.3af,class 0 (Option)
- Power consumption: 1.5W
- Net weight: 0.62kg
- Dimension: 213\*157\*39mm
- Operating humidity: 10~95%
- Storage temperature: up to 60°C

## Package Features

- Qty/CTN: 10 PCS
- N.W/CTN:6.2 KGS
- G.W/CTN: 8.5KGS
- Measurement: 0.037 CBM (0.5% more or less)
- Carton Meas: 430 X 345 X 250 MM

## Certifications

- RoHS
- CE
- FCC
- ISO9001

### **Compatible with the platform**

- AVAYA
- Alcatel-Lucent
- Asterisk
- Broadsoft
- Elastix
- Genesys
- Huawei
- MetaSWITCH
- NEC
- Yearstar
- ZTE
- 3CX