

3-line Gigabit IP Phone

UTT-330PG

Datasheet



UTT-330PG is a located in professional **gigabit** IP phone. UTT-330PG adopt the DSPG chipset, support G.722 wideband encoding; It use with backlit LCD screen to 132 x64 resolution, support Chinese display, provide three SIP accounts, Provide privacy protection. The phone support Tripartite meeting, speed-dial, with abundant function; the phone comes with 12 programmable



keys, and support Extension unit, most can be extended to 192 programmable keys. The phone support earphone, POE, VLAN, VPN. It compatible with the main stream IP PBX, and Easy to install and use, easy to management, to improve office efficiency; Applicable to the head, front desk, the dispatcher, seating engineer and other professional users demand.

Characters

- **3 SIP accounts** (with double color light), through the Broadsoft, deal, Asterisk certified
- 42 buttons (include **12 programmable keys**)
- Support the Tripartite meeting, SMS, voicemail
- Support line sharing (BLA), hold lamp (BLF)
- Supports call waiting and circuit switching
- **Multi-Language Simple Chinese, English, French, Italian, Polish, Portuguese, Russian, Spanish, Turkish etc.**
- Supports a variety of method of automatic configuration: FTP/TFTP/HTTP Auto Provision/TR069
- automatic upgrades, installation is convenient
- Support TLS/HTTPS encryption protocol
- Support POE, RJ-9 earphone, dual network interface
- Support 6 Extension Units 192 programmable keys, Meet the operator work fast and efficient,
- and call monitoring management

Phone features

- Support 3 account lines, hotline
- Support calls holding, calls waiting and calls transfer
- Call transfer (blind turn, turn)
- Caller id, redial, mute, don't disturb
- Auto answer, conference
- Speed-dial, SMS, voicemail
- Message lamp, the state signal, the volume control
- IP direct dial
- Custom ring tone
- Phonebook search/ import /export(300), black list
- Call records: dial calls/received calls/miss calls /
- Friendly user interface
- Support one key quit menu(button c)



ULTRATIVE HK CO., LTD.

E: sales@ultrative.com

T: +86-755-29630367

F: +86-755-29685231

<http://www.ultrative.com>

-
- Support one key to view version number and network state(button c)
 - Support Hardware diagnostics
 - Multi-Language
 - Programmable keys
 - Most support 6 Extension Unit

Advanced features

- Xml phonebook search and import, help users quickly find number and one key to call
- Enterprise phonebook
- LDAP phonebook
- Fuzzy search
- Customizable home screen
- Compatible with the mainstream IP PBX, as: Broadsoft/Avaya/Asterisk
- Intercom, paging
- BLF/BLA
- Intercom, Paging
- Dial plan, call immediately

Audio features

- Wideband encoding: G.722
- Narrow band encoding: G. 711.μ/A, G723.1, G.729AB
- Support VAD, CNG, AEC, PLC, AJB, AGC, such as audio processing ribbon coding
- Full duplex speaker, with automatic echo elimination (AEC)

Network features

- Support SIP v1(RFC2543), v2(RFC3261)
- Support DNS-SRV(RFC3263)
- Support STUN
- 3 DTMF mode: In-band, RFC2833, SIP INFO
- Support the proxy server and point to point connection mode
- Network model: static, DHCP, PPPOE
- Support bridge and router model
- Support TFTP/DHCP/PPPOE terminal
- Support DNS client, built-in NAT/DHCP service
- Login, logout in the web page

Configuration manager

- Support FTP/TFTP/HTTPS automatic configuration
- Support 3 configuration models: web page, phone and auto provision



ULTRATIVE HK CO., LTD.

E: sales@ultrative.com

T: +86-755-29630367

F: +86-755-29685231

http://www.ultrative.com

-
- Support TR069(choice)
 - Load default setting, capture package and system log export

Security

- Support VPN, VLAN QOS(802.1pq)
- LLDP
- Support TLS(Transport Layer Security)
- Support HTTPS(client)
- Support TLS(Transport Layer Security)
- Support information authentication mechanism MD5
- Support AES encryption protocol
- Support phone locks, support the Root/User level management mode

Physical Properties

- DSPG embedded chipset
- 128 x64 graphic dot matrix display, 5 lines shows (including one line display icon)
- 49 buttons(include 12 programmable keys)
- One RJ-9(4P4C) handset interface
- One RJ-9(4P4C) headset interface
- **Two 10/100/1000 Mbps Ethernet interfaces**
- One RJ-45 Extension interface
- The power adapter: AC 100-240V input, DC 5V/1A output
- Support **POE power supply (IEEE 802.3af)**
- Power: 6w
- Net weight: 1.2KG
- Bare machine size: 287mm*214mm*90mm
- The operating environment humidity: 10-90%
- Working environment temperature: 0°C ~ 60°C

Packing

- Qty/CTN:10 PCS
- N.W/CTN: 13.6kg
- G.W/CTN: 14.1kg
- Measurement: 0.081CBM
- Carton Meas: 470mm*450mm*290mm

Certifications



ULTRATIVE HK CO., LTD.

E: sales@ultrative.com

T: +86-755-29630367

F: +86-755-29685231

<http://www.ultrative.com>

- RoHS
 - CE
 - FCC
- ISO9001

ULTRATIVE