

4-line Gigabit IP Phone

UTT-410PG

Datasheet

Gigabit



UTT-410PG is a Clouded IP Phone which support Cloud Management. UTT-410PG is also a pocketed IP Phone which can co-work with Communication Assistant APP to offer mobile extension, switch talking between Cell Phone and IP Phone. UTT-410PG supports Bluetooth, EHS and USB charging. These powerful extended features bring you a completely new



ULTRATIVE HK CO., LTD.

E: sales@ultrative.com

T: +86-755-29630367

F: +86-755-29685231

http://www.ultrative.com

and more efficient work experience in modern offices.

Paperless design integrates a expansion module into the UTT-410PG, which can support as more as 24 programmable keys. Simply flicking the pages can achieve BLF, DTMF, speed dial and other features.

Phone Features

- 4 SIP accounts, Hotline
- Call hold, Call waiting, Call forward, Call return;Call transfer (blind/busy/ask)
- Caller ID display, Redial, Mute, DND
- Auto-answer, 3-way conferencing
- Speed dial, SMS, Voice mail
- Message Waiting Indication LED
- Tone scheme, Volume control
- Direct IP call without SIP proxy
- Ring tone selection /import /delete
- Black list, Hand-free indicator.
- Call history: dialed /received /missed (50 -entries);
- Multi-Language e.g. Chinese, English, Russian, France etc .
- Soft keys programmable, Supports PC control

Advanced Features

- Cloud Management, Cell Phone Communication Assistant APP, BWM36 (EHS & Bluetooth).
- XML Phone Book search and input & output
- Enterprise phone book(800 entries)
- LDAP phone book

IP PBX System Integration

- Busy lamp field (BLF), BLF list
- Bridged line appearance (BLA)
- DND & Forward synchronization
- Intercom, Paging, Music on hold
- Call pickup, Dial Plan, Call recording Anonymous call, Anonymous call rejection
- Network conference, Distinctive ringtone

Codes and Voice Features

- Wideband Codec: G.722



-
- Narrowband codec: G.711 μ /A, G.723.1, G.726, G.729AB, iLBC, VAD, CNG, AEC, AGC
 - Full-duplex

Security

- LLDP, VLAN QoS (802.1pq), VPN(L2TP)
- Transport Layer Security (TLS)
- Digest authentication using MD5/MD5-sess
- Secure configuration file via AES encryption
- Phone lock for personal privacy protection
- Admin/User 2-level configuration mode

Network Features

- SIP v1 (RFC2543), v2 (RFC3261)
- DNS SRV (RFC3263)
- NAT Traversal: STUN mode
- DTMF: In-Band, RFC2833, SIP Info, Auto
- HTTP/HTTPS Web Management
- IP Assignment: Static/DHCP/PPPoE
- Bridge/Router mode for PC port
- TFTP/DHCP/PPPoE client
- DNS client, NAT/DHCP server

Management

- Auto-provision via FTP/TFTP/HTTP/HTTPS
- SNMP V1/2 , TR069 optional
- Configuration: browser/phone/auto-provision
- Trace package and system log export

Physical Features

- 240x160 graphic LCD, 4 level contrast
- 47 keys, including 8 programmable keys
- 20 LEDs: 1* status light, 4* account lights, 1* message light, 1* headset light, 8*programmable lights, 4* function lights,
- 1* speaker lights, Wall-mountable
- 1*RJ-9 handset port
- 1*RJ-9 headset port
- 2xRJ45 10/100/1000M **gigabit** Ethernet ports
- Power adapter: AC 100~240V input and
- DC 12V/1A output
- USB port only support DC 5V feature



ULTRATIVE HK CO., LTD.

E: sales@ultrative.com

T: +86-755-29630367

F: +86-755-29685231

<http://www.ultrative.com>

-
- Power over Ethernet ,IEEE 802.3af, class 0
 - Power consumption: 2.5-3.5W
 - Net weight: 1.37KG
 - Dimension: 287x214x90MM
 - Operating humidity: 10~95%
 - Storage temperature: up to 60°C

Package Features

- Qty/CTN: 10 PCS
- N.W/CTN: 13.7KG
- G.W/CTN: 16.94KG
- Carton Meas: 485*460*300MM

Certifications

- FC
- CE
- RoHS

ULTRATIVE