

4 Lines Business IP Phone

UTT-410P Datasheet



UTT-410P adopt the DSPG chipset, support G.722 wideband encoding; It use with backlit LCD screen to 240 * 160 resolution, support Chinese display, provide four SIP accounts, Provide privacy protection. The phone support Tripartite meeting, speed-dial, with abundant function; the phone comes with 8 programmable keys, and support Extension unit, most can be extended to 192 programmable keys. The phone support earphone, POE, VLAN, VPN. It compatible with the main stream IP PBX, and Easy to install and use, easy to management, to improve office efficiency; Applicable to the head, front desk, the dispatcher, seating engineer and other professional users demand.

Key Features

- Adopt the DSPG chipset
- 2 100BASE-T Ethernet interfaces, support POE power supply
- 3.1 inch 240 * 160 resolution LCD screen, Fourth-order grayscale with backlight
- High-fidelity sound quality: handle HD and HD hands-free, HD encoding
- 4 SIP accounts, support BLF/BLA, VPN
- Support up to 6 extension sets, 192 keys
- Support wall hung

Details

- Adopt the DSPG chipset

- 2 100BASE-T Ethernet interfaces, support POE power supply
- 3.1 inch 240 * 160 resolution LCD screen, Fourth-order grayscale with backlight
- High-fidelity sound quality: handle HD and HD hands-free, HD encoding
- 4 sip accounts, support BLF/BLA, VPN
- Most support 6 Extension Unit, 192 programmable keys
- Through the BroadSoft, Avaya, Asterisk, Alcatel, Yeastar, Digium compatibility certification

Characters

- 4 accounts (with double color light)
- 46 buttons (include 8 programmable keys)
- Support the Tripartite meeting, SMS, voicemail
- Support line sharing (BLA), hold lamp (BLF)
- Supports call waiting and circuit switching
- Multi-Language
- Supports a variety of method of automatic configuration: FTP/TFTP/HTTP Auto Provision/TR069 automatic upgrades, installation is convenient
- Support TLS/HTTPS encryption protocol
- Support POE, RJ-9 earphone, dual network interface
- Most support 6 Extension Unit, 192 programmable keys, Meet the operator work fast and efficient, and call monitoring management

Phone features

- Support 4 account lines, hotline
- Support calls holding, calls waiting and calls transfer
- Call transfer (blind turn, turn)
- Caller id, redial, mute, don't disturb
- Auto answer, conference
- Speed-dial, SMS, voicemail
- Message lamp, the state signal, the volume control
- IP direct dial
- Custom ring tone
- Phonebook search/ import /export(300), black list
- Call records: dial calls/received calls/miss calls /
- Friendly user interface
- Support one key quit menu(button c)
- Support one key to view version number and network state(button c)
- Support Hardware diagnostics
- Multi-Language
- Programmable keys
- Most support 6 Extension Unit

Advanced features

- Xml phonebook search and import, help users quickly find number and one key to call
- Enterprise phonebook
- LDAP phonebook
- Fuzzy search
- Customizable home screen

- Compatible with the mainstream IP PBX, as: Broadsoft/Avaya/Asterisk
- Intercom, paging
- BLF/BLA
- Intercom, Paging
- Dial plan, call immediately

Audio features

- Wideband encoding: G.722
- Narrow band encoding: G. 711.μ/A, G723.1, G.729AB
- Support VAD, CNG, AEC, PLC, AJB, AGC, such as audio processing ribbon coding
- Full duplex speaker, with automatic echo elimination (AEC)

Network features

- Support SIP v1(RFC2543), v2(RFC3261)
- Support DNS-SRV(RFC3263)
- Support STUN
- 3 DTMF model: In-band, RFC2833, SIP INFO
- Support the proxy server and point to point connection mode
- Network model: static, DHCP, PPPOE
- Support bridge and router model
- Support TFTP/DHCP/PPPOE terminal
- Support DNS client, built-in NAT/DHCP service
- Login, logout in the web page

Configuration manager

- Support FTP/TFTP/HTTPS automatic configuration
- Support 3 configuration models: web page, phone and auto provision
- Support TR069(choice)
- Load default setting, capture package and system log export

Security

- Support VPN, VLAN QOS(802.1pq)
- LLDP
- Support TLS(Transport Layer Security)
- Support HTTPS(client)
- Support TLS(Transport Layer Security)
- Support information authentication mechanism MD5
- Support AES encryption protocol
- Support phone locks, support the Root/User level management mode

Physical Properties

- DSPG embedded chipset
- 3.1 inch 240 * 160 resolution LCD screen, Fourth-order grayscale with backlight
- 46 buttons (include 8 programmable keys)
- One RJ-9(4P4C) handset interface
- One RJ-9(4P4C) headset interface
- Two 100BASE-T Ethernet interfaces
- One RJ-45 Extension interface

- The power adapter: AC 100-240V input, DC 5V/1A output
- Support POE power supply (IEEE 802.3af)
- Power: 6w
- Net weight: 1.37KG
- Bare machine size: 287mm*214mm*90mm
- The operating environment humidity: 10-90%
- Working environment temperature: 0°C ~ 60°C

Packing

- Qty/CTN: 10 PCS
- Carton Meas: 500x480x320MM,
- Measurement:0.068CBM(0.5% more or less)
- N.W/CTN:12.50KGS
- G.W/CTN:13.50KGS

Certifications

- RoHS
- CE
- FCC
- ISO9001