
Intercom Security IP Phone

UTT-710P

Datasheet



IP Intercom UTT-710P is well developed according to customers requirements based on VOIP Phone. It has Fashion classic aluminum wire drawing surface shell with the design of waterproof, dustproof, and anti-dismantle. The traits of strong compatibility and supporting extra access swiping card device make it perfectly to be used in bank, subway, power plant, mine, prison, steel companies and so on. It is the best choice and highly cost effective for customers' projects requirements in this industry.

FACTORY IP ADDRESS:

This equipment's factory IP address is using:

Static IP address **192.168.1.153**

Username: **root**

Password: **root**

Features



ULTRATIVE HK CO., LTD.

E: sales@ultrative.com

T: +86-755-29630367

F: +86-755-29685231

http://www.ultrative.com

-
1. IP65, Waterproof, Dustproof.
 2. Adopted aluminum surface shell and cast iron bottom case design which has strong structure to anti-destroy.
 3. High quality voice communication with built-in all kinds of standard speech code.

Details

Key Features:

- One key to dial emergency call for help, realize the bi-directional full-duplex voice intercom.
- Panel adopts advanced wire drawing aluminum alloy material, high strength damage resistant button, strong and durable.
- Support POE power supply and the external power supply.
- Embedded wall or mounted in the wall, to avoid cable leakage users, to ensure that the internal network information security, provide and remote configuration.
- Built-in speaker and high sensitive microphone, support hand-free calls and receive emergency broadcast
- Adopted seal design, waterproof and dustproof level is IP65.
- Support extra access security device, multi-functions provide more perfect service to industry customers.

Phone Features:

- WEB support Multi-Language
- 1 SIP account, Hotline
- Call hold, Call waiting, Call forward
- Call transfer (blind/busy/ask)
- Mute, DND
- Auto-answer, 3-way conferencing
- 1 DSS programmable key (Speed dial, Intercom etc.)
- Volume control
- Direct IP call without SIP proxy
- Default Ring tone 1 selection/import/delete
- Custom Warning Ring tone 2 selection/import/delete
- Time setting(SNTP/SIP Server/Manual)
- Support SIP main/standby server

Advanced Features:

- 1 key to restore the factory value
- 1 DSS programmable key(Speed dial, Intercom etc.)
- 2 input and 2 output control interface, can connect other security equipment
- 1 recording interface, 1 custom warning ring tone interface(using Ring tone 2)



IP PBX System Integration:

- Busy lamp field (BLF), BLF list
- Bridged line appearance (BLA)
- DND & Forward synchronization
- Intercom, Paging, Music on hold
- Call pickup, Dial Plan, Call recording Anonymous call, Anonymous call rejection

Codes and Voice Features:

- Wideband Codec: G.722
- Narrowband codec: G.711u/A, G.723.1
- G.726, G.729a/b, iLBC
- VAD, CNG, AEC, AGC
- Full-duplex,

Security:

- LLDP, VLAN QoS (802.1pq),VPN(L2TP)
- Transport Layer Security (TLS)
- Digest authentication using MD5/MD5-sess
- Secure configuration file via AES encryption
- Phone lock for personal privacy protection
- Admin/User 2-level configuration mode

Network Features:

- SIP v1 (RFC2543), v2 (RFC3261)
- DNS SRV (RFC3263)
- NAT Traversal: STUN mode
- DTMF: In-Band, RFC2833, SIP Info, Auto
- HTTP/HTTPS Web Management
- IP Assignment: Static/DHCP/PPPoE
- Network support Bridge mode
- TFTP/DHCP/PPPoE client
- DNS client, NAT/DHCP server

Management:

- Auto-provision via FTP/TFTP/HTTP/HTTPS
- SNMP V1/2 , TR069 optional
- Configuration: browser/phone/auto-provision
- Trace package and system log export

Physical Features:

- 1 DSS programmable key(Speed dial, Intercom etc.)



ULTRATIVE HK CO., LTD.

E: sales@ultrative.com

T: +86-755-29630367

F: +86-755-29685231

<http://www.ultrative.com>

-
- 1 LED lights,
 - 1 light touch button(Remote factory value)
 - 1xRJ45 10/100M Ethernet ports
 - Power adapter: AC 100~240V input and
 - DC 12V/1A output
 - Power over Ethernet ,IEEE 802.3af,class 0
 - Net weight: 0.52KG, Gross weight: 0.65KG
 - Dimension: 162x112x40MM
 - Operating humidity: 10~95%
 - Storage temperature: up to 60°C

Certifications:

- RoHS, CE, FCC

ULTRATIVE