

IP Door Phone

UTT-720

Datasheet



IP Door Phone UTT-720 is the newest indoor VoIP intercom which professional designed as the requirements from industry users. The device has the characteristic of well compatibility with different platform, offering users a convenient service.

UTT-720 is dust proof, water proof and dismantles prevention, having a fashion appearance and high protection. UTT-720 is a bond of door opening by long-distance DTMF, Password and RFID. Its powerful performance, stability and reasonable price make it a perfect choice of industry user.

NOTE: UTT-720-PRT, **P** is POE, **R** is Reader (optional), **T** is Touchpad (optional).

FACTORY IP ADDRESS:

This equipment's factory IP address is using:

Static IP address **192.168.1.153**

Username: **root**

Password: **root**



Key Features

- Support embedded or wall-mounted installation.
- High-fidelity sound quality, HD codec, Full duplex hands-free calls;
- WEB supports multi-language: Chinese, Russian, French, etc.
- 2 SIP accounts, support 3-way conferencing;
- 2*RJ45 standard Ethernet Ports(LAN/PC), Support PoE;
- Backlit Digital Keyboard, can provide dial-up or password input(Option);
- *Built-in RFID reader; Indoor open-door interface and external power supply interface;
- User-defined DSS keys, which can be set up to Speedy dial, intercom etc.
- Support Plug-and-Play, auto-provision, remote maintenance and management;

Phone Features

WEB Support Multi-language

Support 2 Lines Talking

DND, Hot line

Auto-answer, 3-way conferencing

Direct IP call without SIP proxy

Custom DSS Key (Speed Dial / Intercom etc)

Time setting (SNTP/SIP Server/Manual)

Full-duplex Talking, Dial with digital keypad

Support switching SIP server & Second server

WEB Volume control

Advanced Features

Built-in RFID Reader

Built-in Indoor-open interface

Built-in External Power interface

Built-in Relay

Open the Door ways: DTMF/PWD/RFID Card

SN-SG Log, Remote access list

Support RFID Card

IP PBX System Integration

DND & Call Transfer

Intercom, Paging

Anonymous call, Anonymous call rejection

Network conference, Distinctive ring tone,

Call pickup, Dial Plan, Call recording

Intercom, Paging, Music on hold

Codes and Voice Features

Wideband Codec: G.722



Narrowband codec: G.711μ/A, G.723.1

G.726, G.729AB,VAD, CNG, AEC, AGC

Full-duplex,

Network Features

SIP v1 (RFC2543), v2 (RFC3261)

SIP connection: Proxy mode & Peering Points mode, DNS SRV (RFC3263)

Redundant server support

NAT Traversal: STUN mode

DTMF: In-Band, RFC2833, SIP Info, Auto

HTTP/HTTPS Web Management

IP Assignment: Static/DHCP/PPPoE

Bridge/Router mode for PC port

Telnet/HTTP/HTTPS server

DNS client, NAT/DHCP server

Management

Auto-provision via FTP/TFTP/HTTP/HTTPS

SNMP V1/2, TR069

Configuration: browser/phone/auto-provision

Trace package and system log export

Security

802.1x, VLAN QoS (802.1pq)

Transport Layer Security (TLS)

Digest authentication using MD5/MD5-sess

Secure configuration file via AES encryption

Phone lock for personal privacy protection

Admin/User 2-level configuration mode

Physical Features

1*Digital Keypad, backlit digital (Option)

1*Speaker Key or DSS key

1*Power Light, 1*Network & SIP Light

1*Talking status light

2*RJ-45 10/100M (LAN/PC)

Support PoE: IEEE802.3af class 0

Embedded or wall-mounted installation

Power: 12V/1A DC

RFID/ IC Card

Minimized Power: 4W

Maximum Power: 6W



ULTRATIVE HK CO., LTD.

E: sales@ultrative.com

T: +86-755-29630367

F: +86-755-29685231

<http://www.ultrative.com>

Operating humidity: -30~60 °C

Storage temperature: up to 60 °C

Relative Humidity: 10-90%

Package Features

Qty/CTN: 20PCS

N.W/CTN:9.4KG

G.W/CTN: 12KG

Measurement: 0.068CBM(0.5% more or less)

Dimension: 162X112X41MM

Carton Meas: 365X365X270MM

Certifications

CE, FCC, RoHS

Compatible with the platform

AVAYA

Alcatel-Lucent

Asterisk

Broadsoft

Elastix

Genesys

Huawei

MetaSWITCH

NEC

Yearstar

ZTE

3CX