



- (1) Dual stream encoding / H.264 compression mode
 - (2) 1/4-inch 1.0 Megapixel OV9712 CMOS
 - (3) Include 3.6mm fixed lens
 - (4) IR view distance: 10m (12pcs leds)
 - (5) 1MP:1280*720 D1:640*480 CIF:320*240
 - (6) Support Multi-Screen software and CMS
- Built-in Pan/tilt, horizontally 355°, vertically 90°, Support TF Card (Max 32GB)

Model		UTT-Eye02L
	Item	Household IP Camera
	Device Type	1.0 Megapixel CMOS sensor
	Size	1/4 inch
	Effective Pixels	1MP:1280*720 D1:640*480 CIF:320*240
	B/W	Yes
Min.Scene Illumination	Color	0.5LUX (IR ON)
	IR sensitivity	Yes
	IR-CUT	Yes
Lens	Lens	3.6mm
	Viewing Angle	Horizontal 355°, Vertical 90°
Linux System		Internal Linux system
Day/Nigh	IR distance	10M
Functions	Motion Detection	Yes
	BLC	Yes
	AGC	Auto
	White Balance	Auto
S/N Ratio	S/N Ratio	>50dB
Video Compression	Compression	H.264
	Picture Resolution	1MP:1280*720@25FPS D1:640*480@25FPS CIF:320*240@25FPS
	Bit Rate	80K-2Mbps

Audio	Compression	G.711
	Two way audio	Yes
Network	Ethernet	Ethernet (10/100 Base-T),RJ-45 connector
	Safety	IP address filtering, User level password protection, The user access log
Software	WEB Browser	Microsoft Internet Explorer 6.0 and above, google, firefox etc.
	Mobile Phone	Support iPhone, Android
	Remote	Support DDNS, P2P
	Protocal	TCP,UDP,IP,HTTP,SMTP,DHCP,DNS,DDNS,ARP,ICMP,POP3,NTP,RTP, RTCP
	Image enhancement	Auto White Balance, Backlight compensation, Brightness, Contrast, Saturation adjusted
	Subtitles input	Support channel name, date/time
	Flip Config	Up/down, Left/right
	Software Management	CMS and the devices Compatible with ONVIF
Audio/ Alarm		
	Audio	Two way audio
	equipment	Built-in MIC, horn
	Audio input/output	one channel audio input, one channel audio output
	Alarm way	Motion Detection:Configure motion detection area, detecting sensitivity is adjustable Cover alarm: The alarm sensitivity is adjustable
	Alarm processing	The control center to monitor, Go to PTZ preset pos, Send E-mail, Log record, SD card storage etc.
Physical properties		
	Accessories	Power adapter, Network cable, Stand, Operation manual, CD, Screw bag
	Power Consumption	DC 5V/2A
	Temperature	-20°C~60°C
	Humidity	-10%-80%
	Weight	KG
	Dimension	L*W*H
	Certification	CE,FCC