

5.8G WIFI

2 Lines Hotel WIFI IP Phone

WS118-P Datasheet



WS118-P is a small-screen-based wireless hotel IP phone, it has fashion and technological appearance, excellent voice quality, and powerful features, and it is a new generation of intelligent phones to replace of the hotel traditional desktop terminals, It accomplished the powerful telephony features by cooperating with the communications platform. Such as the call transfer, hotline, three-party conference calling, speed dial, voice mail, Do Not Disturb, etc.

WS118-P IP phones support defined 10 programmable keys, and it can define according to the hotel different needs, such as hotel all kind of equipment service hotline



(housekeeping, ticketing, switchboard, food and beverage, etc.), the hotel special features (alarm clock, voice mail, etc.)

Key Features

1. Wireless working frequency 5.8GHz.
2. Support 10 programmable keys.
3. Multi-language, e.g. Chinese, English, Russian, France etc.
4. 2 SIP accounts and support three-way conference, SMS.
5. Excellent bracket and wall-mountable.
6. 1xLAN, PoE, RJ9Headset.
7. Support 15 paperless programmable keys.
8. XML/LDA, BLF/BLA, Search someone in the Phone book.
9. Auto-provision, HTTP/TFTP/FTP, TR069.

Phone Features

2 SIP accounts, Hotline
Call hold, Call waiting, and Call forward, call return
Call transfer (blind/busy/ask)
Caller ID display, Redial, Mute, DND
Auto-answer, 3-way conferencing
Speed dial, SMS, Voicemail
Message Waiting Indication LED
Tone scheme, Volume control
Direct IP call without SIP proxy
Ring tone selection/import/delete
Black list, Hand-free indicator
Call history: dialed/received/missed (50 -entries);
Multi-Language
Soft keys programmable, Supports PC control

Advanced Features

XML Phone Book search and input & output
Enterprise phone book (800 entries)
LDAP phone book
Functions customizable keys
Support up to 15 paperless programmable keys

IP PBX System Integration

Busy lamp field (BLF), BLF list
Bridged line appearance (BLA)
DND & Forward synchronization
Intercom, Paging, Music on hold



Call pickup, Dial Plan, Call recording Anonymous call, Anonymous call rejection

Network conference, Distinctive ringtone

Codes and Voice Features

Wideband Codec: G.722

Narrowband codec: G.711 μ /A, G.723.1

G.726, G.729AB, iLBC

VAD, CNG, AEC, AGC

Full-duplex,

Security

LLDP, VLAN QoS (802.1pq), VPN (L2TP)

Transport Layer Security (TLS)

Digest authentication using MD5/MD5-sess

Secure configuration file via AES encryption

Phone lock for personal privacy protection

Admin/User 2-level configuration mode

Network Features

SIP v1 (RFC2543), v2 (RFC3261)

DNS SRV (RFC3263)

NAT Traversal: STUN mode

DTMF: In-Band, RFC2833, SIP Info, Auto

HTTP/HTTPS Web Management

IP Assignment: Static/DHCP/PPPoE

Bridge/Router mode for PC port

TFTP/DHCP/PPPoE client

DNS client, NAT/DHCP server

WIFI 802.11 a/b/g/n/ac

Management

Auto-provision via FTP/TFTP/HTTP/HTTPS

SNMP V1 / V2, TR069 optional

Configuration: browser/phone/auto-provision

Trace package and system log export

Physical Features

132x64 graphic LCD

31 keys, including 12 digital keys

2x line keys, 1x conference key, 10x programmable keys, 1x redial key, 1x hold key, 1x speaker key, 1x transfer key,

1x message LED



ULTRATIVE HK CO., LIMITED

E: sales@ultrative.com

T: +86-755-29630367

F: +86-755-29685231

http://www.ultrative.com

1x RJ-9 handset port
2xRJ45 10/100M Ethernet ports
Power over Ethernet IEEE 802.3af, class 0
Operating humidity: 10~95%
Storage temperature: up to 60 °C
Power adapter: AC 100~240V input and DC 5V/1A output

Package Features

QTY/CTN: 10PCS

N.W./CTN: 9KG

G.W./CTN: 10KG

Carton Size: 300*400*500 mm

Certifications

RoHS, CE, FCC, ISO9001



Compatible with the platform

AVAYA, Alcatel-Lucent, Asterisk, Broadsoft, Elastix, Genesys, Huawei, MetaSWITCH, NEC, Yearstar, ZTE, 3CX

